

BenQ DLP Projector EH700

Feature High Light

- 4000ANSI Lumens SSI Green Light Source
- Built in Android 9 OS
- Non Driver Wireless Projection support iOS, ChromeOS, WindowOS, Android
- Remote scheduling power on & off
 Increased USB reader to support keyboard, mouse, USB flash drive at a time
- 10W speaker to fulfill spacious classroom



Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/

Display	
Projection System	DLP Single 0.65" 1080P
DMD type	DMD chip
Native Resolution	1920 x 1080 pixels
Brightness	4000 ANSI Lumens
Contrast Ratio*	
	3,000,000 : 1
Display Color	30 Bits/1.07 Billion Colors
Aspect Ratio	Native 16:9 (4 aspect ratio selectable: Auto / 4:3 / 16:9 /16:10)
Light Source	Laser
Light Source life*	Normal 20,000 hrs; ECO 30,000 hrs; SmartEco 20,000 hr
Optical	
Throw Ratio	1.15~1.50
Zoom Ratio	1.3X
Keystone Correction	2D: Auto Vertical +/- 40 degrees, Horizontal +/- 40 degrees
Projection Offset (Full Height)	105.5%
Projection Size	60"-150"
Audio	
Built-in Speaker	10W*I
Smart System	
CPU	Amlogic S905X3
Storage Type	eMMC IGGB
RAM Type	2GB LPDDR4
OS	Android
Special Feature	
Security	Security Bar, Kensington lock
Feature	Built-in Android system, Wireless Projection, 4-split screen, LAN(RJ45), DMS Cloud, DMS Local, 3 USB reader port, 2D keystone (1D Auto), 10W speaker
Compatibility	
Resolution Support	VGA (640 x 480) to 4K UHD (3840 x 2160)
Horizontal Frequency	15K~\35KHz
Vertical Scan Rate	23 ~ 120 Hz
HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p, 2160p
Power	
Power Consumptions	Max. 275W (Normal/typical Mode 200W at 110VAC, ECO Mode at 150W at 110 VAC)
Standby Power consumption	Max.0.5W , or Max.2W at Network Standby
Power Supply	100 ~ 240V AC, 50/60 Hz
Dimension and Weight	
Product Dimensions (WxHxD)	304 x 112 x 241 mm
Product Weight	3.0 Kg +/- 100g
Operation Condition	
Noise Level(Normal or typical/ ECO)	34 /28 dB
Operating Temperature*	0 ~ 40°C
Accessories	
Accessories (Standard)	Remote Control: RCI024 (5],ISM06.001) Wireless USB Dongle (AM EZCS201BS) AAA Battery x2 Power Cord (1.8m) (by region) QSG (4),ISM0.1001) Warranty card (by Region)

Accessories (Optional)

OB

On Screen Display Language
Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Ite
Environment Notice

* The Contrast is measure by Full On Full Off standard.

*LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.



Connectivity



		Qt
1	HDMI-1 (HDMI 2.0 (HDCP 1.4/2.2))	- 1
2	HDMI-2 (HDMI 2.0 (HDCP 1.4/2.2))	- 1
3	LAN (RJ45)	- 1
4	USB-I TypeA (I.5A power/Reader)	- 1
5	USB-2 TypeA (0.9A power/Reader)	- 1
6	USB-3 TypeA (0.9A power/Reader)	- 1
7	USB-4 TypeA (0.9A Wifi dongle; hidden)	- 1
8	USB-5 TypeA (0.9A Service)	- 1
9	RS232 In (D-sub 9pin, male)	- 1
10	Audio out (mini jack)	- 1
П	Type C (C Input DP(Display) ALT Mode)	- 1
12	Speaker 10W	- 1
13	IR Receiver (Front+Top)	2

14 Kensington anti-theft lock slot 15 Security Bar

Dimension

Dimensions

303.5 mm (W) x 241 mm (D) x 112.4 mm (H)













