


INTERACTIVE BOARD I

MODEL: IB-86TD



VERTEX interactive board allows you to deliver interactive presentation or lessons to the audience easily and efficiency. Presentation can be more flexible and dynamic by displaying pictures, videos and objects, or even Excel files and Power point. The presenter can annotation over the spreadsheet, picture or video. VERTEX interactive board come up to maximum 10 points touch, which allows multi-users to share or write on the board simultaneously.



Multi-touch board

New teachnology support maximum 10 points touch board allows multi-user to write on the board simultaneously.



Ultra-narrow frame

Elegant appearance ultra-narrow aluminum alloy frame.



Shortcut keys on both sides

"shortcut keys" on both of left and right sides of the board make user easy to control.



Environment friendly

The interactive board use infrared induction technology which IR LED light source consumes very low power consumption. Also, LED will reduce the emitting light automatically when the board is not be used.



Simultaneously writing and erasing

The user can write by using finger or pen and also erase by hand, dry erase or hotkey.



Anti-light interference

The board can work normally under 30,000 illumination light that ensure brightness is enough for audience.



Free driver

Use HID interface, the user do not need to install any driver.



Powerful whiteboard software

Whiteboard software is a powerful software which allow user write, insert picture, easer and print out. It is easy to use and understand with in a minutes.

INTERACTIVE BOARD



Model IB-86TD Physical Size (Diagonal) 85.9 inch 1764 x 1283 x 47 Weight 16 Kg. 4:3 Aspect Ratio Touch Points Multiple Operating Support single click, double click, right key Writing, Drawing, Annotation, Touch Correction, Free driver Touch Durability >60,000,000 times Touch Object Finger, writing pen, other object Touch Response (Response Time) Single touch less than 7 ms. 32.768 × 32.768 Resolution <2 mm. 180 dots/s Cursor Speed Light Transmittance 100% Minimum Touch Objects >5 mm. Infrared Induction Driver free, calibration free. Waterproof, dustproof, ultra-thin and light Power Supply USB Power Supply DC 4.6V-5.0V < 1W Gesture Recognition Support Windows Gestures Frame Material Steel frame Left and Right sides Shortcut key Connection USB cable Windows XP/7/8/10, Linux: Chrome OS, Mac OS System Requirements CPU Intel P4 Dual Core 2.0, Ram 4GB, Video Memory 128MB, 80 GB of Free Disk Space Physical Dimension 1704x1283x47 1764x1283x56 (With Bracket) (WxHxD) mm. 1859x1389x82 Packaging Dimension (WxHxD) mm. Working temperature: -15°C~49°C, Storage temperature: -20°C~60°C Working humidity: 10%~92%, Storage humidity: 0%~95% Humidity Pen x 2 / USB Cable x 1 (7.5 m.) / Manual x 2 (1 for Bracket, 1 for Interactive Whiteboard) Standard Packaging Software CD x 1 Wall mounting (Standard) Mounting Way CE, RoHS, ISO9001, IEC60950



1. Mobile floor stand mounting (Option)



2. Mobile floor stand mounting with projector mounting (Option)













122/20-21 SOI LATPHRAO 37, LATPHRAO ROAD, BANGKOK, THAILAND Tel.02-938-1051 Fax. 02-938-1633 E-mail: info@vertex.co.th http://www.vertex.co.th



* free calibration เมื่อใช้กับ windows 10 ขึ้นไปและฉายภาพเต็มจอตามที่กำหนด * บริษัทซอสงวนสิทธิในการเปลี่ยนแปลงรายการโดยใม่ต้องแจ้งให้กราบค่วงหน้า รวมถึงซ้อผิดผลาดในการพิมพ์ และผลิตภัณฑ์อาจแตกต่างจากสีจริงเนื่องจากซ้อกำหนดในการพิมพ์

Dealer:

