7/23/2018 about:blank













TH671ST

Home Theater

SPECIFICATIONS

Projection System DLP Single 0.65" Full-HD DMD type DC3 DMD Chip Native Resolution 1920x1080 pixels Brightness 3000 ANSI Lumens Contrast Ratio* 10,000.1 Display Color 1.07 Billion Colors Aspect Ratio Native 169 (5 aspect ratio selectable) Liight Source 240W Lamp Liight Source life* 4000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio 0.69 - 0.83 (100" @ 1.5m) Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Offset Projection Size (Clear Focus / Mo"-120" / 300" Maximum) Audio Built-in Speaker Security Bar Feature Security Bar Feature ShortThrow Lens (100" @ 1.5m), 16.67ms Low Input Lag. LumiExpert™, SW Stereo Speaker, ID Keystone, Setup Wizard Compatibility Resolution Support VGA (640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility NTSC, PAL, SECAM, PAL60 Power Power Power Comsumption (Mav/Normal/ 480, 480, 576, 567p, 720p, 1080, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption Normal < 0.5W Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Unigensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 400C Accessories Accessories (Standard) Power Cord/GA cable (1.8m)Remote Control (RCVD13) AAA Battery x 2 Lens Cover x 1 User Manual CDQuick Start Guide/Warranty, Card Accessories (Optional) Spare Lamp KitColling Mount/Wireless FHD KitDLP 3D Glasses (GDC5)Carry Bag	Display	
Native Resolution 1920x1080 pixels Brightness 3000 ANSI Lumens Contrast Ratio* 10,000-1 Display Color 1.07 Billion Colors Aspect Ratio Native 169 (5 aspect ratio selectable) Light Source 240W Lamp Light Source 16e* 4000/10000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio 0.69 - 0.83 (100° @ 1.5m) Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Offset 500.5% ± 2.5% Projection Offset 500.5% ± 2.5% Projection Size (Clear Focus / 60°-120° / 300° Maximum) Audio Built-in Speaker 5W x 500 May 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support 15 - 102KHz Vertical Fequency 15 - 102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 1800, 4800, 150 WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15 - 102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility NTSC, PAL, SECAM , PAL60 Power Power Comsumption Max/Normal/ 620 Max 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Compatibility 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (27 kg) Operating Temperature 0 ~ 400C Accessories (Standard) Power Cord/GA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x I User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Projection System	DLP Single 0.65" Full-HD
Brightness 3000 ANSI Lumens Contrast Ratio* 10,000:1 Display Color 1,07 Billion Colors Aspect Ratio Native 16:9 (§ aspect ratio selectable) Light Source 240W Lamp Light Source life* 4000/10000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio 0.69 - 0.83 (100" @ 1.5m) Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / Maximum) 60"~120" / 300" Audio Built-in Speaker 5W x I Special Features Security Bar Securi	DMD type	DC3 DMD Chip
Contrast Ratio* 10,000:1 Display Color 1.07 Billion Colors Aspect Ratio Native 16.9 (5 aspect ratio selectable) Light Source 240W Lamp Light Source 10,000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio 0.69 - 0.83 (100" @ 1.5m) Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / 60"~120" / 300" Maximum) Audio Built-in Speaker 5W x Special Features Security Security Bar Feature Short Throw Lens (100" @ 1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility X480, 480, 576i, 567p, 720p, 1080, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption Max/Normal/ Eco Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Uveight 5.95 lbs (2.7 kg) Operating Temperature 0 ~ 40oC Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1 User Manual CDQuick Start Guide/Warranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Native Resolution	1920x1080 pixels
Display Color Aspect Ratio Native 16.9 (5 aspect ratio selectable) Light Source Light Source 16.* 4000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio O.69 - 0.83 (100" @ 1.5m) Zoom Ratio I.2x Keystone Correction Vertical ± 40 degrees Projection Offset Projection Offset Projection Size (Clear Focus / 60" - 120" / 300" Maximum) Built-in Speaker Sw x I Special Features Security Security Bar Feature Short Throw Lens (100" @ 1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA (640 x 480) to WUXGA_RB (1920 x 1200) "RB = Reduced Blanking Horizontal Frequency I5−102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W, Normal 320W, Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply I00 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) I1.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Dimensions (WxHxD) I1.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Dimensions (WxHxD) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (I.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x I User Manual CDQuick Start Guide/Warranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Brightness	3000 ANSI Lumens
Aspect Ratio Native 16:9 (5 aspect ratio selectable) Light Source 240W Lamp Light Source life* 4000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio 0.69 - 0.83 (100" @ 1.5m) Zoom Ratio 1.2× Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / 60"~120" / 300" Maximum) Audio Built-in Speaker 5W x I Special Features Security Bar Feature Short Throw Lens (100" @ 1.5m), 16.67ms Low Input Lag, LumiExpert™,5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 × 480) to WUXGA_RB (1920 × 1200) "RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480; 480; 576; 567p, 720p, 1080; 1080p Video Compatibility NTSC, PAL, SECAM , PAL60 Power Power Comsumption(Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight 5.95 lbs (2.7 kg) Operating Temperature 0 ~ 400C Accessories Accessories (Standard) Power Cord/GA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × 1User Manual CDQuick Start GuideVarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Contrast Ratio*	10,000:1
Light Source 240W Lamp Light Source life* 4000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio 0.69 - 0.83 (100" @ 1.5m) Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / 60"~120" / 300" Maximum) Audio Built-in Speaker 5VV x Special Features Security Security Bar Feature Short Throw Lens (100" @ 1.5m), 16.67ms Low Input Lag, LumiExpert™,5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM , PAL60 Power Power Comsumption (Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Weight 5.95 lbs (2.7 kg) Operating Temperature 0 ~ 400C Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1User Manual CDQuick Start GuideVarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Display Color	1.07 Billion Colors
Use to Source life* 4000/10000/10000/15000 hours(Normal/Eco/SmartEco/LampSave) Optical Throw Ratio 0.69 - 0.83 (100" @ 1.5m) Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / Maximum) Audio Built-in Speaker Security Security Bar Security Security Bar Security Security Bar Short Throw Lens (100" @ 1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 × 480) to WUXGA_RB (1920 × 1200) *RB = Reduced Blanking Horizontal Frequency 15 - 102KHz Vertical Scan Rate 12 3 - 120 Hz HDTV Compatibility NTSC, PAL, SECAM, PAL60 Power Power Power Comsumption(Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W Power Supply 10 ~ 240V AC Dimension and Weight Product Dimensions (WXHXD) Product Weight Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 400C Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Aspect Ratio	Native 16:9 (5 aspect ratio selectable)
Optical Throw Ratio 0.69 - 0.83 (100" @ 1.5m) Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / Maximum) 60"~120" / 300" Audio Built-in Speaker Short Throw Lens (100" @1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 × 480) to WUXGA_RB (1920 × 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption (Max/Normal/Eco) Max 355W, Normal 320W, Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W	Light Source	240W Lamp
Throw Ratio 20 om Ratio 1.2x	Light Source life*	4000/10000/10000/15000 hours(Normal/Eco/SmartEco/LampSave)
Zoom Ratio 1.2x Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / 60"~120" / 300" Maximum) Audio Built-in Speaker Special Features Security Security Bar Feature Short Throw Lens (100" @1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, I D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM , PAL60 Power Power Comsumption(Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CorndVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWirreless FHD KitDLP 3D Glasses	Optical	
Keystone Correction Vertical ± 40 degrees Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / Maximum) 60"~120" / 300" Audio Built-in Speaker 5W x I Special Features Security Bar Security Security Bar Feature Short Throw Lens (100" @1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, I D Keystone, Setup Wizard Compatibility VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Power Comsumption(Max/Normal/ Eco) Max 355W. Normal 320W. Eco 240W. Eco Standby Power Comsumption Normal < 0.5W	Throw Ratio	0.69 - 0.83 (100"@ 1.5m)
Projection Offset 102.5% ± 2.5% Projection Size (Clear Focus / Maximum) Audio Built-in Speaker 5W x I Special Features Security Security Bar Feature Short Throw Lens (100" @1.5m), 16.67ms Low Input Lag. LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption (Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level (Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power Comp KitDLP 3D Glasses	Zoom Ratio	1.2x
Projection Size (Clear Focus / Maximum) Audio Built-in Speaker 5W x I Special Features Security Security Bar Feature Short Throw Lens (100"@1.5m), 16.67ms Low Input Lag. LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W, Normal 320W, Eco 240W, Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x I User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Keystone Correction	Vertical ± 40 degrees
Maximum) Audio Built-in Speaker 5W x I Special Features Security Security Bar Feature Short Throw Lens (100"@1.5m), 16.67ms Low Input Lag. LumiExpert™,5W Stereo Speaker, ID Keystone, Setup Wizard Compatibility Resolution Support VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Basses) Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x I User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Projection Offset	102.5% ± 2.5%
Built-in Speaker Special Features Security Security Bar Feature Short Throw Lens (100"@1.5m), 16.67ms Low Input Lag. LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 × 480) to WUXGA_RB (1920 × 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × 1User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses		60''~120'' / 300''
Special Features Security Security Bar Feature Short Throw Lens (100"@1.5m), 16.67ms Low Input Lag. LumiExpert™, SW Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 × 480) to WUXGA_RB (1920 × 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Audio	
Security Bar Feature Short Throw Lens (100" @1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 × 480) to WUXGA_RB (1920 × 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W. Normal 320W. Eco 240W. Eco 240W. Eco 240W. Eco 240V. Compatibility Normal Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × 1User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Built-in Speaker	5W x I
Feature ShortThrow Lens (100" @1.5m), 16.67ms Low Input Lag, LumiExpert™, 5W Stereo Speaker, 1D Keystone, Setup Wizard Compatibility Resolution Support VGA(640 × 480) to WUXGA_RB (1920 × 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Bax 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Special Features	
LumiExpert™, 5W Stereo Speaker, ID Keystone, Setup Wizard Compatibility VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM , PAL60 Power Power Comsumption(Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W	Security	Security Bar
Resolution Support VGA(640 x 480) to WUXGA_RB (1920 x 1200) *RB = Reduced Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Feature	
Blanking Horizontal Frequency 15~102KHz Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Compatibility	
Vertical Scan Rate 23 ~ 120 Hz HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Bco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × I User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Resolution Support	
HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Horizontal Frequency	15~102KHz
Video Compatibility NTSC, PAL, SECAM, PAL60 Power Power Comsumption(Max/Normal/ Max 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Vertical Scan Rate	23 ~ 120 Hz
Power Comsumption(Max/Normal/ Max 355W. Normal 320W. Eco 240W. Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × I User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Power Comsumption (Max/Normal/ Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Video Compatibility	NTSC, PAL, SECAM, PAL60
Eco) Standby Power Comsumption Normal < 0.5W Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" × 4.7" × 8.8" (296 × 120 × 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × 1 User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Power	
Power Supply 100 ~ 240V AC Dimension and Weight Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses		Max 355W. Normal 320W. Eco 240W.
Dimension and Weight Product Dimensions (WxHxD)	Standby Power Comsumption	Normal < 0.5W
Product Dimensions (WxHxD) 11.7" x 4.7" x 8.8" (296 x 120 x 224 mm) 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Power Supply	100 ~ 240V AC
Product Weight 5.95 lbs (2.7 kg) Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × I User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Dimension and Weight	
Operation Condition Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Power CordVGA cable (I.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x I User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Product Dimensions (WxHxD)	11.7" x 4.7" x 8.8" (296 x 120 x 224 mm)
Noise Level(Normal/Eco) 33/29 dBA Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × IUser Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Product Weight	5.95 lbs (2.7 kg)
Operating Temperature 0 ~ 40oC Accessories Accessories (Standard) Power CordVGA cable (I.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x IUser Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Operation Condition	
Accessories Accessories (Standard) Power CordVGA cable (I.8m)Remote Control (RCV013) AAA Battery × 2 Lens Cover × IUser Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Noise Level(Normal/Eco)	33/29 dBA
Accessories (Standard) Power CordVGA cable (1.8m)Remote Control (RCV013) AAA Battery x 2 Lens Cover x 1User Manual CDQuick Start GuideWarranty Card Accessories (Optional) Spare Lamp KitCeiling MountWireless FHD KitDLP 3D Glasses	Operating Temperature	0 ~ 40oC
	Accessories	
	Accessories (Standard)	tery x 2 Lens Cover x TUser Manual CDQuick Start GuideWarranty
	Accessories (Optional)	CONTROL OF THE PROPERTY OF THE

- *Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are
- subject to change without notice.

 ** Default picture mode is Game.When 3D is on, picture mode menu only show 3D.When 3D is off, 3D will also

 *The Contrast is measure by Full On Full Off standard.


KEY FEATURES

- Superior Short Throw Projection (100"@ 1.5 meter)
- · Low Input Lag for Smoother Gaming
- LumiExpert for viewing comfort
- Powerful 5W Stereo Speaker
- Native 1080p Full-HD Image Quality





INPUT / OUTPUT TERMINALS



- 1 HDMI-I
- 2 HDMI-2/MHL
- O USB Type A(1.0A power)
- 4 Computer In-I (D-sub I5pin, Female)
- 6 Monitor Out (D-sub 15pin,Female)
- 6 USBType B (Service)
- RS232 In (D-sub 9pin, male)
- Audio In/Out (mini jack)

BenQ.us | BenQ.ca

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.



Because it matters

7/23/2018 about:blank

2/2