

Key Features

- ปิดเครื่องอัตโนมัติ
- อัตราส่วนความคมชัด 22,000:1
- เทคโนโลยี SuperColor™
- โหมด 5 สี
- การปรับค่าสีเหลี่ยมหดตามแนวตั้ง



Product Description

โปรเจคเตอร์วีซีเอ็นรุ่น PA503W นำเสนอคุณภาพของภาพสุดประทับใจเพื่องานนำเสนอที่พัฒนาขึ้น เหมาะสำหรับห้องประชุมขององค์กรธุรกิจขนาดเล็กและชั้นเรียน มาพร้อมความสว่างระดับ 3600 ลูเมนส์และอัตราส่วน contrast ratio ที่ 22,000:1 โปรเจคเตอร์รุ่นนี้ยังรับประกันการฉายที่เก็บรายละเอียดที่ครบถ้วนไม่ว่าจะใช้งานในที่ที่มีปริมาณแสงมากเพียงใด เทคโนโลยี SuperColor™ เฉพาะของวีซีเอ็นยังช่วยให้ภาพที่ฉายออกมามีสีสันครบถ้วน แม่นยำ มีชีวิตชีวาสมจริง ผู้ใช้งานสามารถเลือกโหมดสีได้ถึง 5 โหมด ได้แก่ มาตรฐาน แสงสว่างที่สุด การนำเสนอ ภาพถ่ายและภาพยนตร์ เพื่อเลือกโหมดที่เหมาะสมกับความต้องการมากที่สุดขึ้นอยู่กับฉากที่ต้องการฉาย นอกจากนี้ โหมด SuperEco ที่ช่วยประหยัดพลังงานของโปรเจคเตอร์รุ่นนี้ยังช่วยลดการใช้พลังงานและยืดอายุการใช้งานของหลอดไฟถึง 15,000 ชั่วโมง



SPECIFICATION

Projection system:	0.65" WXGA
Native Resolution:	1280x800
DC type:	DC3
Brightness:	3600 ANSI lumens
Contrast Ratio with SuperEco mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light source life (Nor/SuperEco):	5000/15000
Lamp Watt:	200W
Lens:	F=2.56-2.68, f=22-24.1 mm
Projection Offset:	100% +/-5%
Throw Ratio:	1.55~1.70
Image size:	30" - 300"
Throw Distance:	1m-10.98m(100" @3.34m)
Keystone:	±40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Eco):	27dB
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	2
Composite:	1
Audio-in (3.5mm):	1
HDMI:	1 (Back)

OUTPUT

Monitor out:	1
Audio out (3.5mm):	1
Speaker:	2W

CONTROL

RS232:	1
USB type mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 260W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	2.2kg
Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1
QSG & CD:	QSG: 1 / CD: NA

OPTIONAL ACCESSORY

Air Filter:	RSPL
-------------	------